









SAE 100 R7 EN855 - 0600100



TERMOPLASTICO COSTRUZIONE

- **sottostrato:** poliestere termoplastico
- **rinforzo:** due trecce poliestere alta tenacità
- **copertura:** poliuretano color nero

DN			ref.						A 	B 		
mm	dash	inches	0600100	mm	mm	mm	bar	p.s.i.	bar	bar	mm	g/m
5	-3	3/16	05	5	-	10,6	207	2908	850	827	40	75
6	-4	1/4	06	6,5	-	12,2	190	2750	850	758	30	95
8	-5	5/16	08	8,2	-	14,4	172	2500	760	690	45	125
10	-6	3/8	10	9,8	-	15,9	155	2250	720	620	55	145
12	-8	1/2	12	13,1	-	20,3	138	2000	630	552	75	212

TERMOPLASTIC CONSTRUCTION

- lining: thermoplastic polyester
- reinforcement: two polyester high tenacity braids
- cover: polyurethane black colour

KUNSTOFFAUFBAU


- Seele: Kunststoff aus Polyester
- Druckträger: zwei hochfeste Drahtgeflechte aus Polyester
- Decke: Polyurethan Farbe Schwarze

THERMOPLASTIQUE CONSTRUCTION

- tube intérieur: polyester thermoplastique
- renforcement: deux tresses en polyester haute ténacité
- robe extérieure: polyurethane, couleur noir

TERMOPLASTICOS CONSTRUCCION

- tubo interior: tubo de poliester
- refuerzo: dos trenzas de poliester de elevada resistencia
- cubierta exterior: poliuretano color negro

 -40°C + 93°C
-40°F + 200°F

 142